

E26 Edger Light Installation Instructions

This light is for use on 110 volt Super 7 edgers only. Do not install in 220 volt application!

WARNING: Disconnect power before performing any service or repair.

DANGER: Installation should be performed by a qualified electrician.

Please follow instructions below to install light.

1. Disconnect power from machine.
2. Remove right side handle cover (switch side) and front round vent
3. Disconnect the small light wires from the switch
4. Remove light cover, light bulb and light socket
5. Make sure the front surface where the light goes is clear of any tape, screws and debris
6. Feed the wires from the new light assembly through the original wire hole and up to the vent hole, then over to the switch (inside the housing)
7. Remove the blue tape from the bottom of the light assembly, leaving the white adhesive exposed (this is for heat transfer)
8. Install the light assembly using the provided screw, making sure not to pinch any wires. Make sure it fits flat against the housing.
9. Connect the wires to the switch, black with black and red with white. For the light to be always on, connect the wires with the wires from the power cord; for the light on with the switch, connect the wires with the wires going to the motor.
10. Wrap the switch with electrical tape, and make sure all wires are safely routed away from all moving parts. Re-install the switch cover and vent cover.
11. Plug in and confirm the light functions correctly.

For a video installation guide, please go to store.ussander.com/e26 or scan the link.

